

Water Tank Cleaning Robot

Rajendra B. Khule¹, Sneha Thawari², Ramni Kore³, Amey Purarnik⁴, Nikita Padahye⁵, Tejeswi Meshram⁶

¹ Asst. Prof. Department of Electronics Engineering, KDK College of Engineering, Nagpur (India)

^{2,3,4,5,6} UG Student Department of Electronics Engineering, KDK College of Engineering, Nagpur (India)

Abstract:

Water is the most important and essential commodity a person consumes in his day to day routine. Water is responsible for the sustenance of life. It has been observed that a human being cannot consume all the water available. Only the fresh water which is available can be consumed by humans. Now, interestingly this fresh water is not consumable throughout too ! Only clean water is potable and we can consume it. There have been many methods to store this water in our places and these places are mainly huge storage tanks. These storage tanks are places where a lot of water can be stored and this water should stay clean and potable so we need to clean these tanks.

We are inclined to develop a mechanical system for cleaning water tanks. Our system includes two main mechanisms, which are rack and pinion gear mechanism and reciprocating four bar linkage mechanism

Keywords : Cylindrical water tank, four bar linkage, motor shaft, rack and pinion, PVC brush.

I. INTRODUCTION

1.1 Necessity of Cleaning Water Tank

Every day we use the tank water for brushing and bathing, for cleaning and moping, for washing clothes and in other household chores. With the passage of time, sediments, scale and algae get deposited on the walls, ceiling and floor of the water tank. This deposition contaminates the water and makes it unfit for use. With time algae and bacteria grow and breed in this water infect it and could make us fall sick eventually. Hence water tank cleaning is very important.

1.2 Methods of water tank cleaning

Manual scrubbing in which wall and floor of tank are scrubbed to remove dirt, sediments, fungus and stains, but this method is more tedious and time consuming.

The water tank can also be cleaned by using chemicals to remove the dirt and sediments. The chemicals used may affect the human health.

Pressurized water can be sprayed on the walls of the tank which will remove the dirt from the tank surface.

These methods are time consuming and require more efforts for cleaning.

1.3 Alternate Method

All methods of cleaning water tank as discussed above are time consuming and require more human efforts. So alternate method is required for cleaning purpose which will overcome the drawbacks of all other methods. Therefore we are developing water tank cleaning equipment which requires less time and human efforts for cleaning.

2. MAIN COMPONENTS

2.1 Gear Motor

Gear motor is used to produce high torque with low speed. motor used has specifications as single phase 220V, 15A which produces power of 0.35 HP and frequency of 50 Hz and the shaft speed is 75 rpm.



2.2 Four Bar Linkage

A plane linkage consisting of four links pinned tail to head in a closed loop with lower or closed joints. It is a plane mechanism consisting of four links that form rotating kinematic pairs. The four bar linkage is arranged in such a way that it adjusts the inner diameter of the tank.

2.3 Rack and Pinion

A rack and pinion is a type of linear actuator that comprises a pair of gears which converts rotational motion into linear motion. A circular gear called “the pinion” engages teeth on a linear “gear” bar called “the rack”. Rotational motion applied to the pinion causes the rack to move relative to pinion. Thus the motor attached to the rack is moved in vertical direction along the guide way with the help of handle attached to the pinion.

2.4 Shaft

Shaft made up of mild steel of diameter 15mm is used to transmit rotary motion from motor to the four bar linkage. Holes provided on the shaft, adjust the four bar linkage according to the diameter of the tank.

2.5 Brush

The brushes are made up of Poly Vinyl Chloride (PVC) polymer. Brushes attached to the ends of four bar linkage revolve due to rotation of motor shaft to clean the inner surface of the tank.



3. METHODOLOGY

Firstly whole water is removed from the tank. Detergent is then sprayed on the inner wall of the tank for easy removal of dirt. The whole system is inserted in retracted position into the tank. The four bar linkage is then adjusted according to the tank diameter in such a way that brush at end of the shaft touches the bottom of tank. Now the motor is switched ON. The four bar linkage starts rotating along with the shaft. This causes scrubbing of inner wall of tank by the brush attached to the ends of linkage. For cleaning upper portion of the tank the whole mechanism is reciprocated along the guide ways with the help of handle connected to the rack and pinion arrangement. In this way the tank gets cleaned within minimum time.

4.conclusion

The water tank cleaner was used to clean the water tanks by using rotating brushes. This method was more effective and safe than the conventional methods. This method is capable to clean water tanks within less time and human efforts.

REFERENCES

[1] Robert D. C, and Robert L. W. 2014. The ROV Manual-A User Guide for Remotely

Operated Vehicles. 2n ed. The Boulevard,
Langford Lane, Kidlington, Oxford, OX5 1 GB,
UK: Elsevier Ltd.

[2] Ismadi Ibrahim, 2010. Remotely Operated
Underwater Vehicle (ROV). Fakulti Kejuruteraan
Elektrik. Thesis (Sarjana Kejuruteraan
Elektrik(Mekatronik), UTM.

[3] Kashif, I., Abdullah, S. S., Ayob, S. M. and
Salam, Z. 2010. Single Input Fuzzy Logic
Controller for Unmanned Underwater Vehicle.
Springer Science+Business Media B.V.

[4]<http://www.electronicsforu.com/electronicsforu/circuitarchives>.