

# Effect of Friction in Conveyor Belt Systems in Industries

Prof. Sathe Pooja R.<sup>1</sup>, Gaikwad Abhishek V.<sup>2</sup>, Gaikwad Aditya A.<sup>3</sup>, Gadhave Sneha D.<sup>4</sup>,  
Gadhe Pranav B.<sup>5</sup>, Gagare Rutuja P.<sup>6</sup>

1(FE Engineering Department , SPPU/  
Adsul's Technical Campus, Maharashtra, India.

Email: poojasathe55@gmail.com)

2 (FE Engineering Department , SPPU/  
Adsul's Technical Campus, Maharashtra, India.

Email: abhigaikwad8975@gmail.com)

## Abstract:

Conveyor belt systems are widely used in manufacturing plants, mining industries, food processing units, warehouses, and packaging sectors for continuous material transportation. Friction plays a critical role in the effective functioning of conveyor belts, as it directly influences belt motion, power transmission, material grip, wear, efficiency, and maintenance cost. Proper friction between belt and pulley ensures smooth movement, while excessive or insufficient friction may lead to slippage, overheating, material spillage, and energy losses. This paper studies the effect of friction in conveyor belt systems using Engineering Mechanics principles. Various frictional factors such as belt tension, coefficient of friction, pulley surface condition, load weight, and operating speed are analysed. Results indicate that optimized friction improves performance, safety, and service life of conveyor systems.

**Keywords:** Friction, Conveyor Belt, Industrial Systems, Belt Drive, Power Transmission, Engineering Mechanics

## I. Introduction

Conveyor belts are mechanical systems used for transporting materials from one location to another with minimum manual effort. They are commonly used in mining industries, cement plants, food industries, automobile manufacturing, airports, warehouses, and packaging plants.

A conveyor belt mainly consists of driving pulley, driven pulley, belt, rollers, motor, and supporting frame.

Friction is one of the most important factors in conveyor operation. Adequate friction between the belt and pulley allows torque transmission and material movement.

If friction is too low, the belt slips. If friction is too high, belt wear and energy loss increase.

This paper analyzes the role and effect of friction in conveyor belt systems.

## II. Literature Review

Previous studies in industrial engineering show that conveyor efficiency depends greatly on frictional conditions.

Researchers found that pulley lagging improves grip, rubber belts provide higher friction than smooth surfaces, dust and oil reduce coefficient of friction, belt misalignment increases side friction, and excessive tension causes unnecessary wear.

Modern industries use sensors and automation to monitor belt friction and slippage.

### I. Objectives of the Study

1. To study the effect of friction in conveyor belts.
2. To analyze belt-pulley interaction.
3. To reduce slippage and wear losses.
4. To improve power transmission efficiency.
5. To recommend maintenance methods for industrial belts.

## IV. Theory of Friction in Belt Systems

When a belt passes over a pulley, the ratio of tight side tension to slack side tension is given by:

$$T_1 / T_2 = e^{(\mu\theta)}$$

Where:

- $T_1$  = Tight side tension
- $T_2$  = Slack side tension
- $\mu$  = Coefficient of friction
- $\theta$  = Angle of contact in radians

Power transmitted:

$$P = (T_1 - T_2) v$$

Where:

- $P$  = Power
- $v$  = Belt velocity

Friction force:

$$F = \mu N$$

## V. Factors Affecting Friction

### 1 Belt Material

Rubber belts have higher friction than metal belts.

### 2 Pulley Surface Condition

Rough or lagged pulley surfaces increase grip.

### 3 Belt Tension


Proper tension ensures sufficient contact force.

### 4 Dust, Oil, Moisture

Contaminants reduce friction and cause slip.

### 5 Operating Speed

Very high speed may increase heat and wear.



## VI. Tools Used

MATLAB, ANSYS, SolidWorks, and AutoCAD were considered for analysis.

## VII. Methodology

Three industrial conveyor systems were studied:

1. Mining conveyor
2. Food packaging conveyor
3. Warehouse conveyor

Steps followed:

1. Measure belt load and speed
2. Determine friction coefficient
3. Calculate belt tensions
4. Observe slippage conditions
5. Compare performance under different surfaces

## VIII. Sample Calculation

Given:

- Tight side tension = 1200 N
- Slack side tension = 600 N
- Belt speed = 2 m/s

Power transmitted:

$$P = (1200 - 600) \times 2 = 1200 \text{ W}$$

If coefficient of friction = 0.3 and normal reaction = 2000 N:

$$F = 0.3 \times 2000 = 600 \text{ N}$$

## IX. Results and Analysis

Condition	Performance
Proper Friction	Smooth running
Low Friction	Belt slip
High Friction	Excess wear
Proper Tension	Efficient power transfer
Dusty Surface	Reduced grip

### Findings

1. Moderate friction gives best efficiency.
2. Belt cleaning improves performance.
3. Excessive belt tension shortens life.
4. Lagged pulleys reduce slippage.

## X. Applications

### 1 Mining Industry

Transport of ores and coal.

### 2 Food Industry

Movement of packaged goods.

### 3 Airports

Baggage conveyor systems.

### 4 Automobile Plants

Assembly line transport.

### 5 Warehouses

Parcel movement systems.

## XI. Discussion

Friction is necessary for conveyor belt operation, but it must be optimized.

Benefits of proper friction:

- Smooth belt movement
- Reduced energy loss
- Higher output
- Longer belt life
- Better safety

Challenges:

- Surface contamination
- Misalignment
- Belt aging
- Temperature rise
- Noise and vibration

Regular maintenance is essential.

## XII. Conclusion

This study confirms that friction has a major effect on conveyor belt systems in industries. Proper friction between belt and pulley improves motion, power transmission, and durability, while poor friction causes slip, wear, and energy loss.

Industries should monitor frictional conditions regularly to ensure efficient and safe conveyor operation.

## XIII. Recommendations

1. Maintain proper belt tension.
2. Clean pulley surfaces regularly.
3. Use lagged pulleys where needed.
4. Replace worn belts on time.
5. Use sensors for slip detection.

## XIV. References

1. R. C. Hibbeler, Engineering Mechanics: Statics
2. S. S. Rattan, Theory of Machines
3. Conveyor belt design manuals
4. Industrial maintenance journals
5. Research papers on belt friction systems